



VOLTCRAFT®

VOLTCRAFT® - TOP PERFORMANCE IN EVERY WAY

"Since 1982, our product range has been dynamically adapting to the constant changes in the industry. We commit to offering first-class quality to our customers while delivering an excellent cost-performance ratio. This philosophy remains the cornerstone of Voltcraft's success."

VC130-1 DIGITAL MULTIMETER

Nº 1090519

CE

VERSION 12/21

Robust upcoming unit with manual Measuring range selection. VOLTCRAFT offers something for every user and scope of the appropriate device. From beginners up to the professional model, always on the current state of the art and the usual price. The VC100 series is designed for all measurement tasks in the household and the leisure sector. Even professional tasks can be performed up to 250 V.

HIGHLIGHTS

CAT III 250 V //

2000 counts //

**Standard measurement ranges
V/DC, V/AC, A/DC //**

Resistance //

Diode tester //

Acoustic continuity checker //

Contactless AC voltage checker //

**hFE-transistor test (with optional adapter)
Hold function //**

Low battery display //

**Sturdy housing with soft
rubber protection //**



TECHNICAL DATA

Display	2000 counts (4000 counts with the VC170-1)
Measuring frequency	approx. 2-3 measuring operations/second
Measuring lead length	about 75 cm each
Measuring impedance	>10MΩ (V range)
Operating voltage	9 V block battery
Working conditions g	0°C to 40°C max. 75% rF, non-condensin
Operating altitude	max. 2,000 m
Storage temperature	-10°C to +50°C
Weight	ca. 200 g
Dimensions	(LxWxH) 137 x 72 x 35 (mm)
Measuring category	CAT III 250 V
Degree of contamination	2

Direct voltage, overload protection 250 V

Range VC130-1/150-1	Accuracy	Resolution		Range VC170-1	Accuracy	Resolution
200 mV	±(0.5 % + 8)	0.1 mV		400 mV*	±(0.8% + 8)	0.1 mV
2000 mV		1 mV		4000 mV	±(0.8% + 8)	1 mV
20 V		0.01 V		40 V		0.01 V
200 V		0.1 V		250 V		0.1 V
250 V	±(0,8 % + 8)	1 V	* With the VC170-1, the 400 mV measuring range is only available via the manual measuring range selection.			

Alternating voltage (40 – 400 Hz), overload protection 250 V, Average recording for sinus signal.

Range VC130-1/150-1	Accuracy	Resolution	Range VC170-1	Accuracy	Resolution
200 V	±(1.5 % + 8)	0.1 V	400 mV*	±(2.0% + 10)	0.1 mV
250 V		1 V	4000 mV	±(1.6% + 4)	1 mV
			40 V		0.01 V
			250 V		0.1 V
			* With the VC170-1, the 400 mV measuring range is only available via the manual measuring range selection.		

Direct current, overload protection 1A/250V + 10 A/250 V

Range VC130-1/150-1	Accuracy	Resolution	Range VC170-1	Accuracy	Resolution
200 µA*	±(1.3 % + 2)	0.1 µA	400 µA	±(1.3 % + 2)	0.1 µA
2000 µA		1 µA	4000 µA		1 µA
20 mA		0.01 mA	40 mA	±(1.6 % + 2)	0.01 mA
200 mA	±(1.5 % + 8)	0.1 mA	400 mA		0.1 mA
10 A	±(2.5 % + 10)	0.01 A	4 A	±(2.0 % + 10)	0.01 A
* only with the VC130-1			10 A		0.1 A

Alternating current (only with VC170-1), overload protection 1A/250V + 10 A/250 V, Average recording for sinus signal.

Range (40 - 400 Hz)	Accuracy	Resolution
400 μ A	$\pm(1.6 \% + 5)$	0,1 μ A
4,000 μ A		1 μ A
40 mA	$\pm(2.0 \% + 8)$	0.01 mA
400 mA		0.1 mA
4 A	$\pm(2.6 \% + 4)$	0.001 A
10 A		0.01 A

Resistance, overload protection 250 V, test voltage ca. 0.5 V

Range VC130-1/150-1	Accuracy	Resolution	Range VC170-1	Accuracy	Resolution
200 Ω	$\pm(1.0 \% + 10)$	0.1 Ω	400 Ω	$\pm(1.6 \% + 3)$	0,1 Ω
2000 Ω		1 Ω	4 k Ω	$\pm(1.3 \% + 2)$	0.001 k Ω
20 k Ω		0.01 k Ω	40 k Ω		0.01 k Ω
200 k Ω		0.1 k Ω	400 k Ω		0.1 k Ω
20 M Ω	$\pm(1.3 \% + 7)$	0.01 M Ω	4 / 40 M Ω	$\pm(2.0 \% + 8)$	0.001 / 0.01 M Ω

Temperature (only VC150-1)

Range	Accuracy	Resolution
-40 to 0 $^{\circ}$ C	$\pm(10.4 \% + 7)$	1 $^{\circ}$ C
>0 to 400 $^{\circ}$ C	$\pm(3.3 \% + 4)$	
>400 to 1000 $^{\circ}$ C	$\pm(3.9 \% + 4)$	

Frequency/duty cycle (only with VC170-1), overload protection 250 V

Range	Accuracy	Resolution
10 Hz - 10 MHz max. 10 Vrms	$\pm(0.7 \% + 4)$	0.01 Hz - 0.01 MHz Sensitivity: < 100 kHz = 300 mV > 100 kHz = 600 mV
0.1 - 99.9%		0.1%

Acoustic continuity tester

<10 Ω Permanent sound

Diode test test voltage

U₀ 3.0 V

Diode overload protection/continuity tester:

250 V

Transistor test "hFE"

0 - 1000 β , test voltage U_{ce} 3 V, test current I_{bo} 10 μ A

NCV voltage test

230 V/AC

PACKAGE CONTENT

Digital multimeter // Measurement lines // Battery // Operating instructions

This data sheet is published by Conrad Electronic SE, Klaus-Conrad-Str. 1, D-92240 Hirschau (www.conrad.com).

All rights including translation reserved. Reproduction by any method, e.g. photocopy, microfilming, or the capture in electronic data processing systems require the prior written approval by the editor. Reprinting, also in part, is prohibited. This data sheet represents the technical status at the time of printing.